

# LED Area Light-Edge Series



## Features:

- Clean, low profile design and rugged construction, aesthetically pleasing.
- latest LED performance and advanced LED thermal management technology, and provides both energy efficient and dura.
- Modular led bars, provides wide power range from 60W to 300W, easy maintenance.
- A Knuckle, Bolt-On Arm or Wall mounting design that simplifies the installation of the fixture.
- Optional photocell Control.



## Application

In Urban roads, Industrial areas, Residential areas, Sidewalks, Parking lot, Schools, Gardens and etc.



## Technical Specification

Item No.	KWSDPL060	KWSDPL100	KWSDPL150	KWSDPL200	KWSDPL300
Nominal Power (W)	60	100	150	200	300
Input Voltage (V)	100-277VAC				
Luminous Efficiency (lm/W)	110-120lm/W				
Lumen Output (lm)	7200	12000	18000	24000	36000
LED Light Source	Lumileds or equivalent				
CCT (K)	3000K/4000k/5000K/6500K				
CRI	>80				
Power Factor	0.95				
Driver	Meanwell				
Light Distribution	Type II, Type III, Type V				
IP Rating	IP65				
Body Material	Aluminium + PC lense				
Lifetime(Hrs)	50000				
Dimension(mm)	660x350x185		660x350x185		700x470x185
Warranty	5				
Certification	CE/Cul/DLC				
Finishing	Dark Bronze/White				
Cable	3 core, 18AWG				
Working Temperature	-30°C ~ 50°C				

