


LED Area Light-Shoebox Series



Features:

- Typical shoebox design, the contemporary styling adds to the architectural appeal of any project.
- Add dimming controls for added cost savings and project flexibility.
- Available with an adjustable knuckle-mounting option for façade and flood-light applications.



ADJUSTABLE FITTER MOUNTING



Application

Shopping centers, Car dealerships, General parking lots.



Technical Specification

Item No.	KLYSB90	KLYSB120	KLYSB150	KLYSB200	KLYSB320	KLYSB400
Nominal Power (W)	90	120	150	200	320	400
Input Voltage (V)	100-277Vac 50/60Hz					
Luminous Efficiency (lm/W)	120 lm/W					
Lumen Output (lm)	10800	14400	18000	24000	38400	48000
LED Light Source	Lumileds/Cree					
CCT (K)	4000K/5000K/5700K					
CRI	>70					
Power Factor	0.95					
Driver	Meanwell					
Light Distribution	Type II, Type III, Type V					
IP Rating	IP65					
Body Material	Die cast Aluminium + PC lense					
Lifetime(Hrs)	>50000					
Dimension(mm)	482*320*73	600*435*180	600*435*180	600*435*180	750*600*260	750*600*260
Warranty	5 Years					
Certification	cUL DLC					
Finishing	Black/Brown					
Working Temperature	-30°C ~ 50°C					

