

LED Tube



Features:






- Plug and plat as Type A, no need rewire.
- Or direct AC input as Type B, bypass the existing ballast.
- High efficiency: 110-130LPW.
- Eco-friendly: no UV or IR radiation, mercury free, no flickering.
- Safe transportation: Reliable strong package.
- 50,000 Hrs lifetime, 5 years warranty. UL/CUL/FCC/DLC 4.0 listed.



Application

Office, Home, Car dealerships.

Technical Specification

Item No.	KTXT010	KTXT012	KTXT015	KTXT018	KTXT020
Ref.Photo					
Nominal Power (W)	10	12	15	18	20
Input Voltage (V)	AC 100-277V 50/60Hz				
Luminous Efficiency (lm/W)	110-115lm/W	110-120lm/W	110-120lm/W	110-120lm/W	110-120lm/W
Lumen Output (lm)	1100-1150	1320-1440	1650-1800	1980-2160	2200-2400
LED Light Source	Hongli				
CCT (K)	3000-5000				
CRI	> 80				
Power Factor	0.9				
Driver	Build-in driver				
Beam Angle	220°				
IP Rating	IP20				
Body Material	Glass				
Lifetime(Hrs)	50000				
Dimension(ft)	4ft				
Warranty	5 Years				
Certification	UL/DLC				
Working Temperature	-20°C ~ 45°C				