


# LED Tunnel Light



## Features:

- Die-casting aluminum housing, steady modular design, easy for maintenance.
- High luminaire efficiency of 150-160lm/W.
- Wide power range from 50W-500W.
- IP66 water and dust proof.
- Wide choices of brackets to suit different installation methods.




## Application

Tunnel, Building wallwash, Bridges, Billboard.

## Technical Specification

Item No.	KLYTL050	KLYTL100	KLYTL150	KLYTL200
Ref.Photo				
Nominal Power (W)	50	100	150	200
Input Voltage (V)	AC100-277V 50/60HZ		AC100-277V 50/60HZ	
Luminous Efficiency (lm/W)	150-160 lm/W		150-160 lm/W	
Lumen Output (lm)	7750	15500	23250	31000
Led Light Source	Sanan 5050		Sanan 5050	
CCT (K)	3000-6500K		3000-6500K	
CRI	>75		>75	
Power Factor	0.95		0.95	
Driver	Meanwell / Sosen		Meanwell / Sosen	
Light Distribution	Type II, TypeIII, Type V		Type II, TypeIII, Type V	
IP Rating	IP66		IP66	
Body Material	Aluminum+PC		Aluminum+PC	
Lifetime(Hrs)	50,000		50,000	
Dimension(mm)	340*244.2*144.2mm	340*244.2*144.2mm	372*340*144.2mm	462*340*144.2mm
Warranty	5 Years		5 Years	
Certification	UL		UL	
Working Temperature	-40°C ~ 65°C		-40°C ~ 65°C	

Item No.	KLYTL250	KLYTL300	KLYTL400	KLYTL500
Ref.Photo				
Norminal Power (W)	250	300	400	500
Input Voltage (V)	AC100-277V 50/60HZ		AC100-277V 50/60HZ	
Luminous Efficiency (lm/W)	150-160 lm/W		150-160 lm/W	
Lumen Output (lm)	38750	46500	62000	77500
Led Light Source	Sanan 5050		Sanan 5050	
CCT (K)	3000-6500K		3000-6500K	
CRI	>75		>75	
Power Factor	0.95		0.95	
Driver	Meanwell / Sosen		Meanwell / Sosen	
Light Distribution	Type II, TypeIII, Type V		Type II, TypeIII, Type V	
IP Rating	IP66		IP66	
Body Material	Aluminum+PC		Aluminum+PC	
Lifetime(Hrs)	50,000		50,000	
Dimension(mm)	552.340*144.2mm	642*340*144.2mm	680*552*144.2mm	680*552*144.2mm
Warranty	5 Years		5 Years	
Certification	UL		UL	
Working Temperature	-40°C ~ 65°C		-40°C ~ 65°C	