

# K7 Led Retrofit Kit






## Features:

- Ideal retrofit solution for traditional lighting source while maintain the original historical or unique lighting fixtures.
- IP65, water and dust proof, applicable for total enclosed fixture.
- High Luminaire efficiency of 120lm/W.
- The LED retrofit kit includes the LED light source, LED driver.
- The field adjustable mounting socket or bracket provides maximum flexibility and quick conversion of HID light.
- E39/EX39/E40 socket screw base, 350° adjustable base.
- Different level of CCT to accommodate environmental lighting effect.
- Independent developed driver with Rubycon capacitor.
- Dow Corning RTV-T thermal silicone.

## Application

Area Light , Historic Districts Light , Parks and Open Centers , Campuses , Decorative Post Tops.

## Technical Specification

Item No.	KLMSRK080	KLMSRK100	KLMSRK120
Ref.Photo			
Nominal Power (W)	80	100	120
Input Voltage (V)	AC100-277V		
Luminous Efficiency (lm/W)	120lm/W		
Lumen Output (lm)	9600	12000	14400
LED Light Source	CREE or equivalent		
CCT (K)	2700-6500K		
CRI	>75		
Power Factor	0.9		
Beam Angle	180°		
IP Rating	IP65		
Body Material	Aluminum		
Lifetime(Hrs)	50,000		
Dimension(mm)	150*275*80mm		
Warranty	5 Years		
Certification	UL/DLC		
Working Temperature	-40°C ~ 65°C		