

K9 Led Retrofit Kit






Features:

- Ideal retrofit solution for traditional lighting source while maintain the original historical or unique lighting fixtures.
- IP65, water and dust proof, applicable for total enclosed fixture.
- High Luminaire efficiency of 120lm/W.
- The LED retrofit kit includes the LED light source, LED driver.
- The field adjustable mounting socket or bracket provides maximum flexibility and quick conversion of HID light.
- Different level of CCT to accommodate environmental lighting effect.
- E39/EX39/E40 socket screw base, plus and play.
- Different level of CCT to accommodate environmental lighting effect.
- Independent developed driver with Rubycon capacitor.
- Dow Corning RTV-T thermal silicone.
- Special appearance patent protection.

Application

Area Light , Historic Districts Light , Parks and Open Centers , Campuses , Decorative Post Tops.

Technical Specification

| Item No. | KLMSRK080A | KLMSRK100A | KLMSRK120A |
|----------------------------|---|---|---|
| Ref.Photo |  |  |  |
| Nominal Power (W) | 80 | 100 | 120 |
| Input Voltage (V) | AC100-277V | | |
| Luminous Efficiency (lm/W) | 120lm/W | | |
| Lumen Output (lm) | 9600 | 12000 | 14400 |
| LED Light Source | Lumileds or equivalent | | |
| CCT (K) | 2700-6500K | | |
| CRI | >75 | | |
| Power Factor | 0.9 | | |
| Beam Angle | 120° | | |
| IP Rating | IP65 | | |
| Body Material | Aluminum | | |
| Lifetime(Hrs) | 50,000 | | |
| Dimension(mm) | φ155*H187mm | φ155*H197mm | φ155*H207mm |
| Warranty | 5 Years | | |
| Certification | UL/DLC | | |
| Working Temperature | -40°C ~ 65°C | | |