


Uranus LED Stadium Light



Features:

- Copper heat pipe-riveting and massive 3D HDT fins cooling technology.
- Anti-hurricane level 17.
- 4mm tempered glass.
- 240° angle adjustable mounting bracket.
- Low glare optical, 5°, 10°, 20°, 30°, 60° variety light distribution, available with laser aiming capability.
- Surpass performance of 1000W metal halide.







Application

Stadium, Wharf, Cranes, Port, Airport, Square, Stage etc.



Technical Specification

Content	KBSFSL100	KBSFSL150	KBSFSL250	KBSFSL500
Ref.Photo				
Nominal Power (W)	100	150	250	500
Input Voltage (V)	AC90-260V			
Luminous Efficiency (lm/W)	100lm/W			
Lumen Output (lm)	10000	15000	25000	50000
LED Light Source	CREE/Lumileds/Nichia			
CCT (K)	2700-6000K			
CRI	> 70			
Power Factor	0.95			
Driver	Meanwell/Moso/Inventronics			
Beam Angle	5°/10°/20°/30°/60°			
IP Rating	IP66			
Body Material	Aluminum			
Lifetime(Hrs)	50000			
Dimension(mm)	316*347mm	316*347mm	472*361mm	479*391mm
Warranty	5 Years			
Certification	CE/RoHS			
Working Temperature	-40°C ~ 55°C			